



Energetic Lighting's E2WR and ELYWL series LED surface mount wraps showcase a soft fixture form factor while delivering up to 4200 lumens in their 4-ft length, while drawing only 40 watts of power. These versatile lights can be used for general room lighting, or as a functional work area lights with an all white or silve accent appearance. Installation is quick and simple when mounting into standard ceiling junction boxes. Constructed with a durable steel housing body and LED lifetime rating of at least 50,000 hours, these rugged wrap lights are designed for many years of reliable operation.

## Features

- Different appearance options
- Modern and efficient design
- Reduced glare translucent diffusers
- Suitable for Damp Location use
- 0-10V dimming on E2WR model

## Applications

- Architectural decor
- Overhead task lighting
- Ambient room lighting
- General lighting

## Specification

Order Number	30025	30027	30023
Model Number	ELYWL2-302C	ELYWL2-302S	ELYWL2-301C
Beam Angle	110°	110°	110°
Optical Distribution			
Lumen Output	2100 LM	2100 LM	4356 LM
Luminous Efficacy	105 LM/W	105 LM/W	109 LM/W
Input Power	20 W	20 W	40 W
Input Voltage	120-277 Vac	120-277 Vac	120-277 Vac
Power Factor	>0.9	>0.9	0.93
THD	<0.2	<0.2	0.11
Color Temp (CCT)	4000 K	3000 K	4000 K
Color Rend (CRI)	>80	>80	>80
Lifetime Rating	50000 hours	50000 hours	50000 hours
Warranty	5 Years	5 Years	5 Years
Dimmability	No	No	No
Operating Temp	14 to 122 (°F)	14 to 122 (°F)	14 to 122 (°F)
Environment	Damp Location	Damp Location	Damp Location
DLC			DLC Standard
Weight	6.1 LBS	6.1 LBS	6.1 LBS
Dimensions	24.3"x5.6"x2.0"	24.3"x5.6"x2.0"	48.5"x5.6"x2.0"
Safety Cert	UL	UL	UL