MDF030

Wall Sconce

Features

Housing

Die-formed Cold-rolled Steel Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Glass Creates Excellent Light Distribution and Uniformity LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

Lamp

LED Type: Integrate LED Module , 3000K LED More Color Temperature Option 3500K, 4000K, 5000K GU24 Type: - CFL Bulb, 2700K or 4000K - 9W LED Bulb, 3000K or 4000K

Certification


UL/cUL, ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Limited Warranty on Driver and LED



SUNPARK electronics corp.



LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H X D)	Energy Star
MDF030D-xxxxK	120V	14W	3000K	>80	1050	S. Nickel /	8.7" x 10.2" x 3.8"	Yes
			Frosted glass					

GU24 Type

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H X D)	Energy Star
MDF030-123	120V	1 x 23W GU24	Satin Nickel	Frosted Glass	8.7" x 10.2" x 3.8"	
MDF030-213	120V	2 x 13W GU24	Satin Nickel	Frosted Glass	8.7" x 10.2" x 3.8"	