

Traveyo Series

Traveyo™ LED Street/Area Luminaire - Medium

Rev. Date: V4 09/06/2019

Product Description

The Cree Lighting Traveyo Series changes expectations of the "entry-level" luminaire with solid performance, future-ready engineering and a better than expected lighting experience. The TRVMD LED Street/Area luminaire offers a full range of optics and CCTs to meet the needs of the application while maintaining the familiarity of a traditional cobrahead design. Designed for easy installation, the Traveyo luminaire features tool-less entry, tool-less rotatable 7-pin photocell receptacle, T-level and +/- 5° fixture leveling. Typical replacement: 150-200W HPS.

Applications: Collector roadways, parking lots, and general area spaces

Performance Summary

Initial Delivered Lumens: Up to 11,050

Efficacy: Up to 150 LPW

CRI: Minimum 70 CRI


CCT: 2700K, 3000K, 4000K, 5700K

Limited Warranty*: 5 years standard on luminaire and finish, 10 years optional on luminaire and finish

*See <http://creelighting.com/warranty> for warranty terms

Accessories

Field-Installed
Bird Spikes TRV-BRDGRDM
Backlight Control Shield TRV-BLSM - Provides 1 mounting height cutoff - Black painted aluminum construction - Refer to initial delivered lumen tables for lumen output



Weight

8.6 lbs. (3.9kg)

Ordering Information

Example: TRVMD-A-HT-2ME-8L-27K7-UL-BK-N

TRVMD	A	HT						N	
Product	Version	Mounting	Optic	Lumen Package**	CCT/CRI	Voltage	Color Options	Utility Label/ Receptacle	Options
TRVMD Medium	A	HT Horizontal Tenon	Asymmetric 2ME* Type II Medium 3ME* Type III Medium 4ME* Type IV Medium Symmetric 5ME Type V Medium	8L 8,000 Lumens 10L 10,000 Lumens	27K7 2700K, 70 CRI 30K7 3000K, 70 CRI 40K7 4000K, 70 CRI 57K7 5700K, 70 CRI	UL Universal 120-277V UH Universal 347-480V	BK Black BZ Bronze GY Grey	N Utility Label and NEMA® 7-Pin Photocell Receptacle - External wattage label per ANSI C136.15 - 7-pin receptacle per ANSI C136.41 - Factory connected 0-10V dim leads - Photocell or shorting cap by others	20KV 20kV/10kA Surge Suppression EXPD Expedited Shipping

* Available with Backlight Shield when ordered with field-installed accessory (see table above)

** Lumen Package codes identify approximate light output only. Actual lumen output levels may vary depending on CCT and optic selection. Refer to Initial Delivered Lumen tables for specific lumen values



CREE **LIGHTING**

US: creelighting.com (800) 236-6800

Canada: creelighting-canada.com (800) 473-1234

Product Specifications

CONSTRUCTION & MATERIALS

- Die cast aluminum housing and door
- Tool-less entry
- Mounts on 1.25" (32mm) IP, 1.66" (42mm) O.D. or 2" (51mm) IP, 2.375" (60mm) O.D. horizontal tenon (minimum 8" [203mm] in length) and is adjustable +/- 5° to allow for fixture leveling (includes two axis T-level to aid in leveling)
- Luminaire secures with two mounting bolts
- Comes standard with Utility Label per ANSI C136.15 and 7-pin NEMA® Photocell Receptacle per ANSI C136.41
- **Weight:** 8.6 lbs. (3.9kg)

ELECTRICAL SYSTEM

- **Input Voltage:** 120-277V or 347-480V, 50/60Hz
- **Power Factor:** > 0.9 at full load
- **Total Harmonic Distortion:** < 20% at full load
- Integral 10kV surge suppression protection standard; 20kV surge suppression protection optional
- When code dictates fusing, a slow blow fuse or type C/D breaker should be used to address inrush
- Straight-in wiring to 6-14 AWG terminal block
- Designed with 0-10V dimming capabilities. Controls by others
- **10V Source Current:** 0.15mA
- **Operating Temperature Range:** -40°C - +40°C (-40°F - +104°F)

REGULATORY & VOLUNTARY QUALIFICATIONS

- cULus Listed
- Suitable for wet locations
- Certified to ANSI C136.31-2010, 3G bridge and overpass vibration standards
- Meets CALTrans 611 Vibration testing
- ANSI C136.2 10kV (standard) and 20kV (optional) surge suppression protection tested in accordance with IEEE/ANSI C62.41.2
- Meets FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions
- Luminaire was subjected to the Mixed Flowing Gas for Electrical Contacts Test according to following specifications: ASTM B 845-97, ANSI NCSL Z540-1 3, ISO 17025:2005. No lumen maintenance or color maintenance degradation was noted during testing
- RoHS compliant. Consult factory for additional details
- Dark Sky Friendly, IDA Approved when ordered with 27K7 or 30K7 CCTs. Please refer to <http://darksky.org/fsa/fsa-products/> for most current information
- DLC Premium qualified. Please refer to <https://www.designlights.org/search/> for most current information
-  **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – www.p65warnings.ca.gov

Electrical Data*								
Lumen Package	System Watts 120-480V	Utility Label Wattage	Total Current (A)					
			120V	208V	240V	277V	347V	480V
8L	57	60	0.48	0.28	0.24	0.21	0.16	0.12
10L	77	80	0.65	0.37	0.32	0.29	0.22	0.16

* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347-480V +/- 10%

Traveyo Series Ambient Adjusted Lumen Maintenance ¹					
Ambient	Initial LMF	25K hr Reported ² LMF	50K hr Reported ² LMF	75K hr Estimated ³ LMF	100K hr Estimated ³ LMF
5°C (41°F)	1.01	0.94	0.87	0.80	0.74
10°C (50°F)	1.01	0.94	0.87	0.80	0.74
15°C (59°F)	1.01	0.93	0.86	0.80	0.74
20°C (68°F)	1.00	0.93	0.86	0.79	0.73
25°C (77°F)	1.00	0.93	0.86	0.79	0.73

¹ Lumen maintenance values at 25°C (77°F) are calculated per IES TM-21 based on IES LM-80 report data for the LED package and in-situ luminaire testing. Luminaire ambient temperature factors (LATF) have been applied to all lumen maintenance factors. Please refer to the [Temperature Zone Reference Document](#) for outdoor average nighttime ambient conditions.

² In accordance with IES TM-21, Reported values represent interpolated values based on time durations that are up to 6x the tested duration in the IES LM-80 report for the LED.


³ Estimated values are calculated and represent time durations that exceed the 6x test duration of the LED.

TRVMD LED Street/Area Luminaire - Medium


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<https://creelighting.com/products/outdoor/street-and-roadway/traveyo-series-street>

2ME



CESTL Test Report #: PL13776-001A
TRVXL-A-2ME-30L-40K7-UL**-N**
Initial Delivered Lumens: 31,775




TRVMD-A-2ME-10L-40K7-UL**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,000
Initial FC at grade


Type II Medium Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,950	B2 U0 G2	8,275	B2 U0 G2	8,475	B2 U0 G2	8,525	B2 U0 G2
10L	10,300	B2 U0 G2	10,725	B2 U0 G2	11,000	B2 U0 G2	11,050	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



CESTL Test Report #: PL13936-001A
TRVSM-A-2ME-5L-40K7-UL**-N**
w/TRV-BLSS
Initial Delivered Lumens: 4,753



TRVMD-A-2ME-10L-40K7-UL**-N**
w/TRV-BLSS
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 9,900
Initial FC at grade

Type II Medium w/BLS Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,150	B2 U0 G1	7,450	B2 U0 G1	7,625	B2 U0 G1	7,675	B2 U0 G1
10L	9,275	B2 U0 G2	9,650	B2 U0 G2	9,900	B2 U0 G2	9,950	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens


** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

TRVMD LED Street/Area Luminaire - Medium


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<https://creelighting.com/products/outdoor/street-and-roadway/traveyo-series-street>

3ME



CESTL Test Report #: PL13957-001A
TRVMD-A--3ME-10L-40K7-UL-**-N**
Initial Delivered Lumens: 10,739




TRVMD-A--3ME-10L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,000
Initial FC at grade


Type III Medium Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,950	B2 U0 G1	8,275	B2 U0 G1	8,475	B2 U0 G1	8,525	B2 U0 G1
10L	10,300	B2 U0 G2	10,725	B2 U0 G2	11,000	B2 U0 G2	11,050	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



CESTL Test Report #: PL13937-001A
TRVMD-A--3ME-5L-40K7-UL-**-N**
w/TRV-BLS
Initial Delivered Lumens: 4,834



TRVMD-A--3ME-5L-40K7-UL-**-N**
w/TRV-BLS
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 9,900
Initial FC at grade

Type III Medium w/BLS Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,150	B2 U0 G1	7,450	B2 U0 G1	7,625	B2 U0 G1	7,675	B2 U0 G1
10L	9,275	B2 U0 G2	9,650	B2 U0 G2	9,900	B2 U0 G2	9,950	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens


** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

TRVMD LED Street/Area Luminaire - Medium


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<https://creelighting.com/products/outdoor/street-and-roadway/traveyo-series-street>

4ME



CESTL Test Report #: PL13627-001A
TRVMD-A--4ME-10L-40K7-UL-**-N**
Initial Delivered Lumens: 10,791




TRVMD-A--4ME-10L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,000
Initial FC at grade


Type IV Medium Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,950	B2 U0 G2	8,275	B2 U0 G2	8,475	B2 U0 G2	8,525	B2 U0 G2
10L	10,300	B2 U0 G2	10,725	B2 U0 G2	11,000	B2 U0 G2	11,050	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



CESTL Test Report #: PL14011-001A
TRVMD-A--4ME-10L-40K7-UL-**-N**
w/TRV-BLSM
Initial Delivered Lumens: 4,696



TRVMD-A--4ME-10L-40K7-UL-**-N**
w/TRV-BLSM
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 9,900
Initial FC at grade

Type IV Medium w/BLS Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,150	B2 U0 G2	7,450	B2 U0 G2	7,625	B2 U0 G2	7,675	B2 U0 G2
10L	9,275	B2 U0 G2	9,650	B2 U0 G2	9,900	B2 U0 G2	9,950	B2 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens


** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

TRVMD LED Street/Area Luminaire - Medium


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<https://creelighting.com/products/outdoor/street-and-roadway/traveyo-series-street>

5ME



CESTL Test Report #: PL13780-001A
TRVXL-A--5ME-30L-40K7-UL-**-N**
Initial Delivered Lumens: 31,860



TRVMD-A--5ME-10L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 11,000
Initial FC at grade

Type V Medium Distribution								
Lumen Package	2700K		3000K		4000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
8L	7,950	B3 U0 G2	8,275	B3 U0 G2	8,475	B3 U0 G2	8,525	B3 U0 G2
10L	10,300	B4 U0 G2	10,725	B4 U0 G2	11,000	B4 U0 G2	11,050	B4 U0 G2

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

Luminaire EPA

Horizontal Tenon Mount – Weight: 8.6 lbs. (3.9kg)				
Single	2 @ 90°	2 @ 180°	3 @ 90°	4 @ 90°
Tenon Configuration: If used with Cree Lighting tenons, please add tenon EPA with luminaire EPA				
PD-1H4; PT-1H	PD-2H4(90); PT-2H(90)	PD-2H4(180); PT-2H(180)	PD-3H4(90); PT-3H(90)	PD-4H4(90); PT-4H(90)
0.44	0.73	0.89	1.18	1.46

Tenon EPA

Part Number	EPA
PD Series Tenons	0.09
PT Series Tenons	0.10
WM-2L	0.13
XA-TMDA8	0.19

Tenons and Brackets† (must specify color)	
Square Internal Mount Horizontal Tenons (Aluminum) - Mounts to 4" (102mm) square aluminum or steel poles PD-1H4 – Single PD-3H4(90) – 90° Triple PD-2H4(90) – 90° Twin PD-4H4(90) – 90° Quad PD-2H4(180) – 180° Twin	Round External Mount Horizontal Tenons (Aluminum) - Mounts to 2.375"-3" (60-76mm) O.D. round aluminum or steel poles or tenons - Mounts to 3" (76mm), 5" (127mm), or 6" (152mm) square pole with PB-1A* tenon PT-1H – Single PT-3H(90) – 90° Triple PT-2H(90) – 90° Twin PT-4H(90) – 90° Quad PT-2H(180) – 180° Twin
Wall Mount Brackets - Mounts to wall or roof WM-2L – Extended Horizontal	Direct Arm Pole Adaptor Bracket - Mounts to 3-6" (76-152mm) round or square aluminum or steel poles XA-TMDA8

† Refer to the [Bracket and Tenons spec sheet](#) for more details

* Specify pole size: 3 (3"), 4 (4"), 5 (5"), or 6 (6") for single, double or triple luminaire orientation or 4 (4"), 5 (5") or 6 (6") for quad luminaire orientation

© 2019 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only.
Content is subject to change. Patent www.creelighting.com/patents. Cree® and the Cree logo are registered trademarks of Cree, Inc. Traveyo™ is a trademark of Cree Lighting, A company of IDEAL INDUSTRIES. The UL logo is a registered trademark of UL LLC. The DLC QPL Premium logo are registered trademarks of Efficiency Forward, Inc. NEMA® is a registered trademark of the National Electrical Manufacturers Association.

US: creelighting.com (800) 236-6800

Canada: creelighting-canada.com (800) 473-1234

CREE LIGHTING

A COMPANY OF IDEAL INDUSTRIES, INC.