

XSP Series

XSPLG LED Street/Area Luminaire – Large

Rev. Date: V3 10/18/2019

Product Description

Designed from the ground up as a totally optimized LED street and area lighting system, the XSP Series delivers incredible efficiency without sacrificing application performance. Beyond substantial energy savings and reduced maintenance, Cree achieves greater optical control with our NanoOptic® Precision Delivery Grid™ optic when compared to traditional cobra head luminaires. The XSP Series is the better alternative for traditional street and area lighting with quick payback and improved performance.

Applications: Multi-lane freeways, express ways, major roads, parking lots, and general area spaces

Performance Summary

NanoOptic® Precision Delivery Grid™ optic

Assembled in the U.S.A. of U.S. and imported parts

Initial Delivered Lumens: Up to 23,800

Efficacy: Up to 139 LPW

CRI: Minimum 70 CRI


CCT: 2700K, 3000K, 4000K, 5000K, 5700K

Limited Warranty*: 10 years on luminaire/10 years on Colorfast DeltaGuard® finish

* See <http://creelighting.com/warranty> for warranty terms

Accessories

Field-Installed	
Backlight Control Shield XA-SP2BLS - Provides 1 mounting height cutoff - Polycarbonate construction - Refer to initial delivered lumen tables for lumen output	Bird Spikes XA-SP2BRDSPK



Weight
23.4 lbs. (10.6kg)

Ordering Information

Example: XSPLG-D-HT-2LG-24L-27K7-UL-SV-N

XSPLG	D	HT						N	
Product	Version	Mounting	Optic	Lumen Package**	CCT/CRI	Voltage	Color Options	Utility Label/Receptacle	Options
XSPLG	D	HT Horizontal Tenon	Asymmetric 2LG* Type II Long 2ME* Type II Medium 3ME* Type III Medium 4ME* Type IV Medium	18L 18,000 Lumens 24L 24,000 Lumens	27K7 2700K, 70 CRI 30K7 3000K, 70 CRI 40K7 4000K, 70 CRI 50K7 5000K, 70 CRI 57K7 5700K, 70 CRI	UL Universal 120-277V UH Universal 347-480V	BK Black BZ Bronze SV Silver WH White	N Utility Label and NEMA® 7-Pin Photocell Receptacle - External wattage label per ANSI C136.15 - 7-pin receptacle per ANSI C136.41 - Receptacle leads are factory connected to the driver - Photocell or shorting cap by others	G Small Four Bolt Mounting - Mounts to 1.25" (32mm) IP, 1.66" (42mm) O.D. horizontal tenon J Large Four Bolt Mounting - Mounts to 2" (51mm) IP, 2.375" (60mm) O.D. horizontal tenon Q9/Q8/Q7/Q6/Q5/Q4/Q3/Q2/Q1 Field Adjustable Output - Must select Q9, Q8, Q7, Q6, Q5, Q4, Q3, Q2, or Q1 - Offers full range lumen adjustability - Includes wattage label for setting selected - Refer to pages 8 and 9 for power and lumen values - Luminaire may also be dimmed through 7-Pin receptacle with use of dimming control by others X8/X7/X6/X5/X4/X3/X2/X1 Locked Lumen Output - Must select X8, X7, X6, X5, X4, X3, X2, or X1 - Lumen output is permanently locked to the setting selected - Includes wattage label for setting selected - Refer to pages 8 and 9 for power and lumen values - Dimming is only available through 7-Pin receptacle with use of dimming control by others

* Available with Backlight Shield when ordered with field-installed accessory (see table above)

** Lumen Package codes identify approximate light output only. Actual lumen output levels may vary depending on CCT and optic selection. Refer to Initial Delivered Lumen tables for specific lumen values



US: creelighting.com (800) 236-6800

Canada: creelighting-canada.com (800) 473-1234

CREE LIGHTING

Product Specifications

CONSTRUCTION & MATERIALS

- Die cast aluminum housing
- Tool-less entry
- Mounts on 1.25" (32mm) IP, 1.66" (42mm) O.D. or 2" (51mm) IP, 2.375" (60mm) O.D. horizontal tenon (minimum 8" [203mm] in length) and is adjustable +/- 5° to allow for fixture leveling (includes two axis T-level to aid in leveling)
- Luminaire secures with two 410 stainless steel mounting bolts; optional four point mounting available
- Exclusive Colorfast DeltaGuard® finish features an E-Coat epoxy primer with an ultra-durable black, bronze, silver or white powder topcoat, providing excellent resistance to corrosion, ultraviolet degradation and abrasion
- **Weight:** 23.4 lbs. (10.6kg)

ELECTRICAL SYSTEM

- **Input Voltage:** 120-277V or 347-480V, 50/60Hz
- **Power Factor:** > 0.9 at full load
- **Total Harmonic Distortion:** < 20% at full load
- Integral 10kV surge suppression protection standard
- When code dictates fusing, a slow blow fuse or type C/D breaker should be used to address inrush current
- Consult factory if in-luminaire fusing is required
- Designed with 0-10V dimming capabilities. Controls by others
- **10V Source Current:** 0.15mA
- **Operating Temperature Range:** -40°C - +40°C (-40°F - +104°F)

REGULATORY & VOLUNTARY QUALIFICATIONS

- cULus Listed
- Suitable for wet locations
- Certified to ANSI C136.31-2001, 3G bridge and overpass vibration standards
- Meets CALTrans 611 Vibration testing
- ANSI C136.2 10kV surge protection, tested in accordance with IEEE/ANSI C62.41.2
- Meets FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions
- Luminaire and finish endurance tested to withstand 5,000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- Meets Buy American requirements within ARRA
- RoHS compliant. Consult factory for additional details
- Dark Sky Friendly, IDA Approved when ordered with 27K7 or 30K7 CCTs. Please refer to <https://www.darksky.org/our-work/lighting/lighting-for-industry/fsa/fsa-products/> for most current information
- DLC Premium qualified versions available. Please refer to <https://www.designlights.org/search/> for most current information.
-  **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – www.p65warnings.ca.gov

Electrical Data*										
Lumen Package	Optics	CCT/ CRI	System Watts 120-480V	Utility Label Wattage	Total Current (A)					
					120V	208V	240V	277V	347V	480V
18L	All	All	135	140	1.13	0.65	0.57	0.49	0.39	0.28
24L	All	All	184	180	1.54	0.89	0.77	0.67	0.54	0.39

* Electrical data at 25°C (77°F). Actual wattage may differ by +/- 10% when operating between 120-277V or 347-480V +/- 10%

XSP Series (XSPLG) Ambient Adjusted Lumen Maintenance¹

Ambient	Initial LMF	25K hr Reported ² LMF	50K hr Reported ² LMF	75K hr Reported ² LMF	100K hr Estimated ³ LMF
5°C (41°F)	1.03	1.02	1.02	1.02	1.02
10°C (50°F)	1.03	1.02	1.02	1.02	1.02
15°C (59°F)	1.02	1.01	1.01	1.01	1.01
20°C (68°F)	1.01	1.00	1.00	1.00	1.00
25°C (77°F)	1.00	0.99	0.99	0.99	0.99

¹ Lumen maintenance values at 25°C (77°F) are calculated per IES TM-21 based on IES LM-80 report data for the LED package and in-situ luminaire testing. Luminaire ambient temperature factors (LATF) have been applied to all lumen maintenance factors. Please refer to the [Temperature Zone Reference Document](#) for outdoor average nighttime ambient conditions


² In accordance with IES TM-21, Reported values represent interpolated values based on time durations that are up to 6x the tested duration in the IES LM-80 report for the LED.

³ Estimated values are calculated and represent time durations that exceed the 6x test duration of the LED.


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<http://creelighting.com/products/outdoor/street-and-roadway/xsp-series>

2LG



RESTL Test Report #: PL12765-007B
XSPLG-D--2LG-24L-40K7-UL-**-N**
Initial Delivered Lumens: 23,437




XSPLG-D--2LG-24L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 23,600
 Initial FC at grade


Type II Long Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	17,500	B3 U0 G3	18,100	B3 U0 G3	18,700	B3 U0 G3	18,800	B3 U0 G3	18,800	B3 U0 G3
24L	22,300	B4 U0 G3	23,000	B4 U0 G3	23,600	B4 U0 G3	23,800	B4 U0 G3	23,800	B4 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



RESTL Test Report #: PL12765-008B
XSPLG-D--2LG-24L-40K7-UL-**-N**
w/XA-SP2BLS
Initial Delivered Lumens: 17,373



XSPLG-D--2LG-24L-40K7-UL-**-N**
w/XA-SP2BLS
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 17,500
 Initial FC at grade

Type II Long w/BLS Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	12,950	B2 U0 G2	13,400	B2 U0 G2	13,850	B2 U0 G2	13,900	B2 U0 G2	13,900	B2 U0 G2
24L	16,500	B3 U0 G2	17,000	B3 U0 G3	17,500	B3 U0 G3	17,600	B3 U0 G3	17,600	B3 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens


** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

XSPLG LED Street/Area Luminaire – Large


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<http://creelighting.com/products/outdoor/street-and-roadway/xsp-series>

2ME



RESTL Test Report #: PL12765-003B
XSPLG-D--2ME-24L-40K7-UL-**-N**
Initial Delivered Lumens: 23,168




XSPLG-D--2ME-24L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 23,600
Initial FC at grade


Type II Medium Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	17,500	B3 U0 G3	18,100	B3 U0 G3	18,700	B3 U0 G3	18,800	B3 U0 G3	18,800	B3 U0 G3
24L	22,300	B3 U0 G3	23,000	B3 U0 G3	23,600	B3 U0 G3	23,800	B3 U0 G3	23,800	B3 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



RESTL Test Report #: PL12765-004B
XSPLG-D--2ME-24L-40K7-UL-**-N**
w/XA-SP2BLS
Initial Delivered Lumens: 17,757



XSPLG-D--2ME-24L-40K7-UL-**-N**
w/XA-SP2BLS
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 18,200
Initial FC at grade

Type II Medium w/BLS Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	13,475	B1 U0 G2	13,925	B1 U0 G2	14,400	B1 U0 G2	14,475	B1 U0 G2	14,475	B1 U0 G2
24L	17,200	B2 U0 G3	17,700	B2 U0 G3	18,200	B2 U0 G3	18,300	B2 U0 G3	18,300	B2 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens


** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

XSPLG LED Street/Area Luminaire – Large


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<http://creelighting.com/products/outdoor/street-and-roadway/xsp-series>

3ME



RESTL Test Report #: PL12765-001B
XSPLG-D--3ME-24L-40K7-UL-**-N**
Initial Delivered Lumens: 23,083




XSPLG-D--3ME-24L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 23,600
Initial FC at grade


Type III Medium Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	17,500	B3 U0 G3	18,100	B3 U0 G3	18,700	B3 U0 G3	18,800	B3 U0 G3	18,800	B3 U0 G3
24L	22,300	B3 U0 G3	23,000	B3 U0 G3	23,600	B3 U0 G4	23,800	B3 U0 G4	23,800	B3 U0 G4

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



RESTL Test Report #: PL12765-002B
XSPLG-D--3ME-24L-40K7-UL-**-N**
w/XA-SP2BLS
Initial Delivered Lumens: 16,503



XSPLG-D--3ME-24L-40K7-UL-**-N**
w/XA-SP2BLS
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 16,800
Initial FC at grade

Type III Medium w/BLS Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	12,425	B2 U0 G2	12,850	B2 U0 G2	13,275	B2 U0 G2	13,350	B2 U0 G2	13,350	B2 U0 G2
24L	15,800	B2 U0 G3	16,300	B2 U0 G3	16,800	B2 U0 G3	16,900	B2 U0 G3	16,900	B2 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens


** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

XSPLG LED Street/Area Luminaire – Large


Photometry

All published luminaire photometric testing performed to IESNA LM-79-08 standards. To obtain an IES file specific to your project consult:
<http://creelighting.com/products/outdoor/street-and-roadway/xsp-series>

4ME



RESTL Test Report #: PL12765-005B
XSPLG-D--4ME-24L-40K7-UL-**-N**
Initial Delivered Lumens: 23,195




XSPLG-D--4ME-24L-40K7-UL-**-N**
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 23,600
Initial FC at grade


Type IV Medium Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	17,500	B3 U0 G3	18,100	B3 U0 G3	18,700	B3 U0 G3	18,800	B3 U0 G3	18,800	B3 U0 G3
24L	22,300	B3 U0 G3	23,000	B3 U0 G3	23,600	B3 U0 G3	23,800	B4 U0 G3	23,800	B4 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>



RESTL Test Report #: PL12765-006B
XSPLG-D--4ME-24L-40K7-UL-**-N**
w/XA-SP2BLS
Initial Delivered Lumens: 16,941



XSPLG-D--4ME-24L-40K7-UL-**-N**
w/XA-SP2BLS
Mounting Height: 25' (7.6m) A.F.G.
Initial Delivered Lumens: 17,200
Initial FC at grade

Type IV Medium w/BLS Distribution										
Lumen Package	2700K		3000K		4000K		5000K		5700K	
	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11	Initial Delivered Lumens*	BUG Ratings** Per TM-15-11
18L	12,775	B2 U0 G2	13,225	B2 U0 G2	13,650	B2 U0 G2	13,725	B2 U0 G2	13,725	B2 U0 G2
24L	16,300	B2 U0 G2	16,800	B2 U0 G2	17,200	B2 U0 G3	17,400	B2 U0 G3	17,400	B2 U0 G3

* Initial delivered lumens at 25°C (77°F). Actual production yield may vary between -10 and +10% of initial delivered lumens

** For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>

Luminaire EPA

Horizontal Tenon Mount – Weight: 23.4 lbs. (10.6kg)				
Single	2 @ 90°	2 @ 180°	3 @ 90°	4 @ 90°
Tenon Configuration If used with Cree Lighting tenons, please add tenon EPA with luminaire EPA				
				
PD-1H4; PT-1H	PD-2H4[90]; PT-2H[90]	PD-2H4[180]; PT-2H[180]	PD-3H4[90]; PT-3H[90]	PD-4H4[90]; PT-4H[90]
0.69	1.14	1.38	1.83	2.28

Tenon EPA

Part Number	EPA
PD Series Tenons	0.09
PT Series Tenons	0.10
WM-2L	0.13
XA-TMDA8	0.19

Tenons and Brackets* (must specify color)	
Square Internal Mount Horizontal Tenons (Aluminum) - Mounts to 4" (102mm) square aluminum or steel poles PD-1H4 – Single PD-3H4[90] – 90° Triple PD-2H4[90] – 90° Twin PD-4H4[90] – 90° Quad PD-2H4[180] – 180° Twin	Round External Mount Horizontal Tenons (Aluminum) - Mounts to 2.375"-3" (60-76mm) O.D. round aluminum or steel poles or tenons - Mounts to 3" (76mm), 4" (102mm), 5" (127mm), or 6" (152mm) square pole with PB-1A* tenon PT-1H – Single PT-3H[90] – 90° Triple PT-2H[90] – 90° Twin PT-4H[90] – 90° Quad PT-2H[180] – 180° Twin
Wall Mount Brackets - Mounts to wall or roof WM-2L – Extended Horizontal	Direct Arm Pole Adaptor Bracket - Mounts to 3-6" (76-152mm) round or square aluminum or steel poles XA-TMDA8

* Refer to the [Bracket and Tenons spec sheet](#) for more details

* Specify pole size: 3 {3"}, 4 {4"}, 5 {5"}, or 6 {6"} for single, double or triple luminaire orientation or 4 {4"}, 5 {5"} or 6 {6"} for quad luminaire orientation

XSPLG LED Street/Area Luminaire – Large

Field Adjustable Output (Q9/Q8/Q7/Q6/Q5/Q4/Q3/Q2/Q1) Option Description:

The Field Adjustable Output option enables the street and area luminaire within the XSP Series on this page to be tuned to the exact needs of a particular application through multiple levels of adjustment. When ordered with the Q option, the luminaire will be shipped from the factory at the selected lumen output, will be fully adjustable between the outputs, and will include a wattage label that indicates the wattage of the luminaire at the selected lumen output (Rounded to nearest 10 watts per ANSI C136.15-2015.). Additional dimming functionality is available when a dimming control (by others) is used in the 7-Pin receptacle.

Locked Lumen Output (X8/X7/X6/X5/X4/X3/X2/X1) Option Description:

The Locked Lumen Output option on this page permanently locks the lumen output on the XSP Series street and area luminaire to the setting selected. When ordered with the X option, the luminaire will be shipped from the factory at the lumen output setting selected, and will include a wattage label that indicates the wattage of the setting selected. When this option is selected, the luminaire output is not able to be adjusted in the field except if a dimming control (by others) is used in the 7-Pin receptacle.

Q & X Option Power & Lumen Data – 18L

Q Option Setting	X Option Setting	CCT/CRI	System Watts†		Lumen Values†					Optics Qualified on DLC QPL	
			120-480V	Label Wattage	2LG/2ME/3ME/4ME	2LG w/BLS	2ME w/BLS	3ME w/BLS	4ME w/BLS	Standard	Premium
Q9	N/A (Full Power)	27K7	135	140	17,500	12,950	13,475	12,425	12,775		2LG, 2ME, 3ME, 4ME
		30K7			18,100	13,400	13,925	12,850	13,225		2LG, 2ME, 3ME, 4ME
		40K7			18,700	13,850	14,400	13,275	13,650		2LG, 2ME, 3ME, 4ME
		50K7			18,800	13,900	14,475	13,350	13,725		2LG, 2ME, 3ME, 4ME
		57K7			18,800	13,900	14,475	13,350	13,725		2LG, 2ME, 3ME, 4ME
Q8	X8	27K7	128	130	16,700	12,350	12,850	11,850	12,200		2LG, 2ME, 3ME, 4ME
		30K7			17,300	12,800	13,325	12,275	12,625		2LG, 2ME, 3ME, 4ME
		40K7			17,900	13,250	13,775	12,700	13,075		2LG, 2ME, 3ME, 4ME
		50K7			18,000	13,325	13,850	12,775	13,150		2LG, 2ME, 3ME, 4ME
		57K7			18,000	13,325	13,850	12,775	13,150		2LG, 2ME, 3ME, 4ME
Q7	X7	27K7	121	120	16,000	11,850	12,325	11,350	11,675		2LG, 2ME, 3ME, 4ME
		30K7			16,500	12,200	12,700	11,725	12,050		2LG, 2ME, 3ME, 4ME
		40K7			17,100	12,650	13,175	12,150	12,475		2LG, 2ME, 3ME, 4ME
		50K7			17,200	12,725	13,250	12,200	12,550		2LG, 2ME, 3ME, 4ME
		57K7			17,200	12,725	13,250	12,200	12,550		2LG, 2ME, 3ME, 4ME
Q6	X6	27K7	115	120	15,400	11,400	11,850	10,925	11,250		2LG, 2ME, 3ME, 4ME
		30K7			15,900	11,775	12,250	11,300	11,600		2LG, 2ME, 3ME, 4ME
		40K7			16,500	12,200	12,700	11,725	12,050		2LG, 2ME, 3ME, 4ME
		50K7			16,600	12,275	12,775	11,775	12,125		2LG, 2ME, 3ME, 4ME
		57K7			16,600	12,275	12,775	11,775	12,125		2LG, 2ME, 3ME, 4ME
Q5	X5	27K7	105	110	14,275	10,575	11,000	10,125	10,425		2LG, 2ME, 3ME, 4ME
		30K7			14,750	10,925	11,350	10,475	10,775		2LG, 2ME, 3ME, 4ME
		40K7			15,300	11,325	11,775	10,875	11,175		2LG, 2ME, 3ME, 4ME
		50K7			15,400	11,400	11,850	10,925	11,250		2LG, 2ME, 3ME, 4ME
		57K7			15,400	11,400	11,850	10,925	11,250		2LG, 2ME, 3ME, 4ME
Q4	X4	27K7	95	100	13,025	9,650	10,025	9,250	9,500		2LG, 2ME, 3ME, 4ME
		30K7			13,475	9,975	10,375	9,575	9,825		2LG, 2ME, 3ME, 4ME
		40K7			13,975	10,350	10,750	9,925	10,200		2LG, 2ME, 3ME, 4ME
		50K7			14,025	10,375	10,800	9,950	10,250		2LG, 2ME, 3ME, 4ME
		57K7			14,025	10,375	10,800	9,950	10,250		2LG, 2ME, 3ME, 4ME
Q3	X3	27K7	85	90	11,875	8,800	9,150	8,425	8,675		2LG, 2ME, 3ME, 4ME
		30K7			12,275	9,075	9,450	8,725	8,950		2LG, 2ME, 3ME, 4ME
		40K7			12,725	9,425	9,800	9,025	9,300		2LG, 2ME, 3ME, 4ME
		50K7			12,775	9,450	9,825	9,075	9,325		2LG, 2ME, 3ME, 4ME
		57K7			12,775	9,450	9,825	9,075	9,325		2LG, 2ME, 3ME, 4ME
Q2	X2	27K7	76	80	10,725	7,925	8,250	7,625	7,825		2LG, 2ME, 3ME, 4ME
		30K7			11,075	8,200	8,525	7,875	8,075		2LG, 2ME, 3ME, 4ME
		40K7			11,475	8,500	8,825	8,150	8,375		2LG, 2ME, 3ME, 4ME
		50K7			11,525	8,525	8,875	8,175	8,425		2LG, 2ME, 3ME, 4ME
		57K7			11,525	8,525	8,875	8,175	8,425		2LG, 2ME, 3ME, 4ME
Q1	X1	27K7	67	70	9,525	7,050	7,325	6,775	6,950		2LG, 2ME, 3ME, 4ME
		30K7			9,850	7,300	7,575	7,000	7,200		2LG, 2ME, 3ME, 4ME
		40K7			10,200	7,550	7,850	7,250	7,450		2LG, 2ME, 3ME, 4ME
		50K7			10,250	7,575	7,900	7,275	7,475		2LG, 2ME, 3ME, 4ME
		57K7			10,250	7,575	7,900	7,275	7,475		2LG, 2ME, 3ME, 4ME

† Electrical and lumen data at 25°C (77°F). Actual wattage and lumen output may differ by +/-10% when operating between 120-277V or 347-480V +/-10%

XSPLG LED Street/Area Luminaire – Large

Field Adjustable Output (Q9/Q8/Q7/Q6/Q5/Q4/Q3/Q2/Q1) Option Description:

The Field Adjustable Output option enables the street and area luminaire within the XSP Series on this page to be tuned to the exact needs of a particular application through multiple levels of adjustment. When ordered with the Q option, the luminaire will be shipped from the factory at the selected lumen output, will be fully adjustable between the outputs, and will include a wattage label that indicates the wattage of the luminaire at the selected lumen output (Rounded to nearest 10 watts per ANSI C136.15-2015.). Additional dimming functionality is available when a dimming control (by others) is used in the 7-Pin receptacle.

Locked Lumen Output (X8/X7/X6/X5/X4/X3/X2/X1) Option Description:

The Locked Lumen Output option on this page permanently locks the lumen output on the XSP Series street and area luminaire to the setting selected. When ordered with the X option, the luminaire will be shipped from the factory at the lumen output setting selected, and will include a wattage label that indicates the wattage of the setting selected. When this option is selected, the luminaire output is not able to be adjusted in the field except if a dimming control (by others) is used in the 7-Pin receptacle.

Q & X Option Power & Lumen Data – 24L

Q Option Setting	X Option Setting	CCT/CRI	System Watts*	Label Wattage	Lumen Values†					Optics Qualified on DLC QPL	
			120-480V		2LG/2ME/3ME/4ME	2LG w/BLS	2ME w/BLS	3ME w/BLS	4ME w/BLS	Standard	Premium
Q9	N/A (Full Power)	27K7	184	180	22,300	16,500	17,200	15,800	16,300		2LG, 2ME, 3ME, 4ME
		30K7			23,000	17,000	17,700	16,300	16,800		2LG, 2ME, 3ME, 4ME
		40K7			23,600	17,500	18,200	16,800	17,200		2LG, 2ME, 3ME, 4ME
		50K7			23,800	17,600	18,300	16,900	17,400		2LG, 2ME, 3ME, 4ME
		57K7			23,800	17,600	18,300	16,900	17,400		2LG, 2ME, 3ME, 4ME
Q8	X8	27K7	174	170	21,600	16,000	16,600	15,300	15,800		2LG, 2ME, 3ME, 4ME
		30K7			22,300	16,500	17,200	15,800	16,300		2LG, 2ME, 3ME, 4ME
		40K7			22,900	16,900	17,600	16,300	16,700		2LG, 2ME, 3ME, 4ME
		50K7			23,000	17,000	17,700	16,300	16,800		2LG, 2ME, 3ME, 4ME
		57K7			23,000	17,000	17,700	16,300	16,800		2LG, 2ME, 3ME, 4ME
Q7	X7	27K7	164	160	20,700	15,300	15,900	14,700	15,100		2LG, 2ME, 3ME, 4ME
		30K7			21,300	15,800	16,400	15,100	15,500		2LG, 2ME, 3ME, 4ME
		40K7			21,900	16,200	16,900	15,500	16,000		2LG, 2ME, 3ME, 4ME
		50K7			22,100	16,400	17,000	15,700	16,100		2LG, 2ME, 3ME, 4ME
		57K7			22,100	16,400	17,000	15,700	16,100		2LG, 2ME, 3ME, 4ME
Q6	X6	27K7	156	160	20,100	14,875	15,500	14,275	14,675		2LG, 2ME, 3ME, 4ME
		30K7			20,700	15,300	15,900	14,700	15,100		2LG, 2ME, 3ME, 4ME
		40K7			21,300	15,800	16,400	15,100	15,500		2LG, 2ME, 3ME, 4ME
		50K7			21,400	15,800	16,500	15,200	15,600		2LG, 2ME, 3ME, 4ME
		57K7			21,400	15,800	16,500	15,200	15,600		2LG, 2ME, 3ME, 4ME
Q5	X5	27K7	143	140	18,500	13,700	14,250	13,125	13,500		2LG, 2ME, 3ME, 4ME
		30K7			19,000	14,050	14,625	13,500	13,875		2LG, 2ME, 3ME, 4ME
		40K7			19,600	14,500	15,100	13,925	14,300		2LG, 2ME, 3ME, 4ME
		50K7			19,700	14,575	15,200	13,975	14,375		2LG, 2ME, 3ME, 4ME
		57K7			19,700	14,575	15,200	13,975	14,375		2LG, 2ME, 3ME, 4ME
Q4	X4	27K7	128	130	17,400	12,875	13,400	12,350	12,700		2LG, 2ME, 3ME, 4ME
		30K7			17,800	13,175	13,700	12,650	13,000		2LG, 2ME, 3ME, 4ME
		40K7			18,400	13,625	14,175	13,075	13,425		2LG, 2ME, 3ME, 4ME
		50K7			18,500	13,700	14,250	13,125	13,500		2LG, 2ME, 3ME, 4ME
		57K7			18,500	13,700	14,250	13,125	13,500		2LG, 2ME, 3ME, 4ME
Q3	X3	27K7	116	120	15,800	11,700	12,175	11,225	11,525		2LG, 2ME, 3ME, 4ME
		30K7			16,200	12,000	12,475	11,500	11,825		2LG, 2ME, 3ME, 4ME
		40K7			16,700	12,350	12,850	11,850	12,200		2LG, 2ME, 3ME, 4ME
		50K7			16,800	12,425	12,925	11,925	12,275		2LG, 2ME, 3ME, 4ME
		57K7			16,800	12,425	12,925	11,925	12,275		2LG, 2ME, 3ME, 4ME
Q2	X2	27K7	103	100	14,325	10,600	11,025	10,175	10,450		2LG, 2ME, 3ME, 4ME
		30K7			14,725	10,900	11,350	10,450	10,750		2LG, 2ME, 3ME, 4ME
		40K7			15,100	11,175	11,625	10,725	11,025		2LG, 2ME, 3ME, 4ME
		50K7			15,300	11,325	11,775	10,875	11,175		2LG, 2ME, 3ME, 4ME
		57K7			15,300	11,325	11,775	10,875	11,175		2LG, 2ME, 3ME, 4ME
Q1	X1	27K7	91	90	13,075	9,675	10,075	9,275	9,550		2LG, 2ME, 3ME, 4ME
		30K7			13,450	9,950	10,350	9,550	9,825		2LG, 2ME, 3ME, 4ME
		40K7			13,825	10,225	10,650	9,825	10,100		2LG, 2ME, 3ME, 4ME
		50K7			13,925	10,300	10,725	9,875	10,175		2LG, 2ME, 3ME, 4ME
		57K7			13,925	10,300	10,725	9,875	10,175		2LG, 2ME, 3ME, 4ME

* Electrical and lumen data at 25°C (77°F). Actual wattage and lumen output may differ by +/-10% when operating between 120-277V or 347-480V +/-10%

© 2019 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. Cree® and the Cree logo are registered trademarks of Cree, Inc. NanoOptic® and Colorfast DeltaGuard® are registered trademarks, and Precision Delivery Grid™ is a trademark of Cree Lighting, A company of IDEAL INDUSTRIES. The UL logo is a registered trademark of UL LLC. NEMA® is a registered trademark of the National Electrical Manufacturers Association. The DLC QPL Premium logo is a registered trademark of Efficiency Forward, Inc.

US: creelighting.com (800) 236-6800

Canada: creelighting-canada.com (800) 473-1234

CREE  **LIGHTING**

A COMPANY OF **IDEAL INDUSTRIES, INC.**