LED Garden Light



Specifications

Color 5000K

CRI ≥70

Input Voltage 110V-277V

Operating Temp. -40°F to 140°F

Wattage 20W, 35W, 50W, 100W

Beam Angle 100*140°

Power Factor >0.93

Warranty 5-year warranty

Ordering Information

Model #	Wattage	Lumen	Color
AGL-260-W020-Y1-Z1 (3000K)	20W	1980	3000K
AGL-260-W020-Y1-Z1 (4000K)	20W	2030	4000K
AGL-260-W020-Y1-Z1 (5000K)	20W	2080	5000K
AGL-260-W035-Y1-Zn(3000K)	35W	3270	3000K
AGL-260-W035-Y1-Zn(4000K)	35W	3370	4000K
AGL-260-W035-Y1-Zn(5000K)	35W	3460	5000K
AGL-325-W50-Y1-Z1 (3000K)	50W	4470	3000K
AGL-325-W50-Y1-Z1 (4000K)	50W	4470	4000K
AGL-325-W50-Y1-Z1 (5000K)	50W	4700	5000K
AGL-325-W100-Y1-Z1 (3000K)	100W	9950	3000K
AGL-325-W100-Y1-Z1 (4000K)	100W	10200	4000K
AGL-325-W100-Y1-Z1 (5000K)	100W	10400	5000K

Application:

Features

- Application: Pedestrian street, factory, schools, garden, courtyard, hotel, parking lot, public park
- Lighter in weight
- Cost-effective
- Dimmable
- Samsung LED chips producing brighter lighting
- IP65 for wet locations
- Photocell optional
- 5-year warranty


Product Compliance & Certifications:


- ETL
- DLC 4.2

Description

The Garden Light is a cost-effective and high performance option for various applications such as pedestrian streets, factories, schools, gardens, and more. It has an elegant appearance, excellent structure, and is lighter in weight. It is IP65 rated for wet locations.

Dimensions





Beam Angle: 100*140°