



Specifications

Efficacy > 120 LM/W

CRI > 80

Color 5000K

Wattage 100W, 150W, 200W

Beam Angle 110°

Input Voltage 110V-277V (50-60Hz)

Operating Temp. -40°F-122°F

Size 10.83" x 12.22" x2.26"

17.7" x 13.7" x 2.34" 17.7" x 13.7" x 2.34"

Warranty 5-year warranty

Ordering Information

Product #	Wattage	Lumen
AFL-10S-100W-A-L-P-5000K	100W	12000
AFL-15S-150W-A-L-P-5000K	150W	18000
AFL-20S-200W-A-L-P-5000K	200W	24000

Features

- Compact and light weight, wide range of wattage
- Higher wattage models can be used for sports field lighting
- Samsung LED diodes
- Yoke mount bracket with easy lighting direction adjustment
- IP65 for wet location

Product Compliance & Certifications:

- ETL
- DLC

Description

Aleddra's DMD Flood Light is designed with versatility in mind. It's compact and light weight. It comes in a wide range of wattage, from 100W to 200W, for all types of outdoor lighting applications. The higher wattage models can be used for sports field lighting. Its yoke mount bracket provides easy adjustment for different lighting direction. When mounting on the building, it can be used as a good wallpack fixture. It can also be used on the ground or as a wall wash light. The default beam angle is 110 degrees.