# Slim Vapor Tight



### Specifications

**Size** 2ft, 4-ft, 8-ft

Efficacy 120lm/w

Color 5000K

**CRI** ≥82

Beam Angle 270°

Input Voltage 90-305VAC

Power Factor >0.9

**Operating Temp**. -14°F to 104°F

Rated Life 50,000 hours

**Warranty** 5-year warranty

### **Dimensions**

Туре	Length	Height	Width
2-ft, 20W	23.62"	2.36"	3.70"
4-ft, 36W	47.24"	2.36"	3.70"
8-ft, 70W	94.48"	2.36"	3.70"

## Max. Daisy Chain Power

Input Voltage	Total Max. Power of Connection		
120V	400W		
277V	1000W		

### **Features**

- Sizes: 2-ft, 4-ft, 8-ft
- Unique design and appearance, wide beam angle
- Various Product Applications: Parking lots, gas stations, supermarkets, office indoor lighting and more.
- Motion Sensor (optional)
- Emergency Backup (optional)
- 180 minutes on battery (6W light output)
- Battery check by remote control
- 5-year warranty

#### **Product Compliance & Certifications:**

- UL certified
- IP65 rated
- DLC 4.2

### Description

The Slim Vapor Tight is the best quality enclosure. It has a unique appearance and has a wide beam angle. Its built-in aluminum heat sink provides cooling and improves safety. It is IP65 rated. Optional features include the Motion Sensor and the Emergency Backup.

## **Ordering Information**

Product #	Size	Wattage	Lumen	Color
AVT-2FT-20W-50K AVT-2FT-20W-50K-MS AVT-2FT-25W-50K-EB AVT-2FT-25W-50K-MS+EB AVT-4FT-36W-50K AVT-4FT-36W-50K-MS AVT-4FT-45W-50K-FB	2-ft 2-ft 2-ft 2-ft 4-ft 4-ft 4-ft	20W 20W 25W 25W 36W 36W 45W	2560 2560 3200 3200 4600 4600 5760	5000K 5000K 5000K 5000K 5000K 5000K
AVT-4FT-45W-50K-MS+EB AVT-8FT-70W-50K AVT-8FT-70W-50K-MS	4-ft 8-ft 8-ft	45W 45W 70W 70W	5760 5760 8960 8960	5000K 5000K 5000K 5000K
AVT-8FT-70W-50K-EB AVT-8FT-70W-50K-MS+EB	8-ft 8-ft	70W 70W	8960 8960	5000K 5000K

<sup>\*</sup>MS (Motion Sensor) \*EB (Emergency Backup)

<sup>\*</sup>Other colors made to order