


Project	
Schedule	Date
Notes	

DESCRIPTION

naturalLED[®] Utility Strip Light provides the perfect solution for your lighting needs. The LED utility strip light maximizes energy savings and is designed for multiple applications including retrofit and new construction. The fixture is 48-inches long and can be installed end to end. The LED Utility Strip Light can be used for warehouse, parking garages, stairwells, offices, hallways and many other applications in industrial, commercial and residential. Types of installation include ceiling, wall, chain or cable mounting. Our Utility Strip Light is very versatile, efficient and is available in 40 watt, 4000K and 5000K delivering up to 4,387 lumens with excellent, consistent color. Our Utility Strip Light features an acrylic opaque lens with an aluminum body.



FEATURES

- DLC Qualified
- For Damp Location
- L70 Rated Chip for over 100,000 projected life hours
- Uniform and consistent color: ANSI C78.377-2017
- Easy installation with multiple mounting options
- Mounting brackets/clips for ceiling, wall, cable, and chain
- 1/2" knockouts for end
- Motion / Daylight Sensor
- Material: Aluminum and Opaque lens
- Input line voltage: 120-277V / 347V
- Power Factor: >0.9
- Input current: 0.34A (@120V)
- THD: <20%
- Dimmable: 1-10V
- Operating temperature: -4°F - 131°F
- 50,000 rated life hours

ACCESSORIES



APPLICATIONS

- Warehouses
- Pathway Lighting
- Parking Garage
- Stairwells and Hallways
- Retail Lighting

WARRANTY

- 5 Year Warranty


Ordering Information		EXAMPLE: LED-FXUSL40/48FR/840/MV-SEN					
LED	FX	USL	40	48FR	840	MV	SEN
LED	Category	Series	Wattage	Size/ Lens	CRI/Color Temp	Multiple Voltage	Accessory
	FX Fixture	USL Utility Strip Light	40 40W	48FR 48 inch Frosted	8 CRI 80 40 4000K	MV 120-277V	SEN Sensor

ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	Color Temp (K)	Lumens (lm)	Size	Beam Angle	Dim	Rated Hrs	Damp Location	DLC
40	7593	LED-FXUSL40/48FR/840/MV	4000K	4,387	2.5"x48"	110°	1-10V	50,000	•	S
40	7594	LED-FXUSL40/48FR/850/MV	5000K	4,518	2.5"x48"	110°	1-10V	50,000	•	S
40	9253	LED-FXUSL40/48FR/840/MV-SEN*	4000K	4,387	2.5"x48"	110°	1-10V	50,000	•	S
* Microwave Sensor Included										
Voltage 347V										
40	7602	LED-FXUSL40/48FR/840/347	4000K	4,407	2.5"x48"	110°	1-10V	50,000	•	S

SPECIFICATIONS



Size	Length (L)	Width (W)	Height(H)
4 ft	48" (1219mm)	2.5" (63.5mm)	2.8" (73mm)

MOUNTING / ACCESSORIES

SOLD SEPARATELY

Emergency Driver

- 7334 BAEM15-48BC/MV-A (LED Emergency Backup Driver 120-277V)



Step Down Driver

- P10138 BA-GETR480/277-250W (347-480V to 277V Step Down Driver)




Motion Sensor

- P10091 SEN-UM05/ANT5 (Motion/ Daylight Sensor)




Wireguard

- P10303 WG-USL/48/WH (Wireguard)



PACKAGE


Master Pack: 1 pc



PHOTOMETRICS CHART

USL40 (40 Watt)

DLC




	Illuminance at a Distance	
	Center Beam fc	Beam Width
2.5R	191 fc	7.5 ft 11.8 ft
5.0R	47.7 fc	15.1 ft 23.6 ft
7.5R	21.2 fc	22.6 ft 35.4 ft
10.0R	11.9 fc	30.1 ft 47.2 ft
12.5R	7.63 fc	37.6 ft 59.1 ft
15.0R	5.30 fc	45.2 ft 70.9 ft

Vert. Spread: 112.8°
Horiz. Spread: 134.1°

USL40 (40 Watt) with sensor

DLC



	Illuminance at a Distance	
	Center Beam fc	Beam Width
2.5R	191 fc	7.5 ft 11.8 ft
5.0R	47.7 fc	15.1 ft 23.6 ft
7.5R	21.2 fc	22.6 ft 35.4 ft
10.0R	11.9 fc	30.1 ft 47.2 ft
12.5R	7.63 fc	37.6 ft 59.1 ft
15.0R	5.30 fc	45.2 ft 70.9 ft

Vert. Spread: 112.8°
Horiz. Spread: 134.1°