

EXL4

Slim LED Exit Sign

Product Description

The NICOR EXL4 Series presents a very slim design, only 1" deep! This UL924 code compliant solution for exit and emergency requirements offers all code requirements in a smaller package. The evenly illuminated exit sign is available with red or green stencils. The maintenance free nickel-cadmium battery provides 90 minutes of back up power. The EXL4 Series offers flexible installation for surface ceiling, wall or end mount options along with field adjustable chevrons for universal configuration based on your application's directional needs.

Construction

- Injection molded thermoplastic ABS housing, UL-94-V-0 rated material

Optical System

- Uniform lighting with specially designed plastic diffuser to prevent shadowing

Electrical

- Operating temperature rating of 5°F to 104°F (-15°C to 40°C)
- Maintenance-free nickel-cadmium battery provides 90-minute emergency operation
 - Recharges in 24 hours
- 120/277VAC Dual voltage operation, 60Hz input
- Fully-illuminated 6" letter height with 3/4" stroke
- Includes test switch/power indicator light

LED

- Light engine provides consistently bright and even EXIT legend illumination with red or green LEDs

Finish

- White textured thermoplastic housing
- Available with either red or green lettering

Installation

- Surface ceiling, wall or end mount installation options
- Snap-in mounting bracket
- Universal mounting plate with EZ quick connect
- Universal knockout pattern provided on housing for surface mount install
- Field-installable, removable chevron directional indicators for all configurations
- Supplied with two faces for single or double face installation

Compliance

- UL 924
- Listed for damp locations

Warranty

- 1-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

PRODUCT INFORMATION

Input Voltage:	120/277 VAC
Power Draw:	1.6 W
Emergency Battery:	90 Minutes

Ordering Information

Example: EXL41UNVWHR2

Series	Version	Voltage	Housing Color	Letter Color	Number of Faces
EXL4	1 (Version 1)	UNV (120/277VAC)	WH (White)	G (Green)	2 (Single and Double)
				R (Red)	

Specifications and dimensions subject to change without notice

Project _____

Catalog _____

Type _____

Date _____

