

JOB NAME:	_
DATE: _	 _
TYPE: _	

DIMENSIONS:

6"(H) x 2.7"(D)



FLS-10W-50K-BR FLS-10W-30K-BR FLS-10W-50K-WH FLS-10W-30K-WH



A modern replacement for weatherproof PAR38 lamp holders and 100W quartz fixtures

ELECTRICAL SPECIFICATIONS:

Voltage: 100~130VAC, 50/60 Hz

Wattage: 10WPower factor: 0.95Efficacy: 95LM/W

HOUSING SPECIFICATIONS:

- Die-cast aluminum with powder coat finish
- White Reflector
- · Rotating directional hood
- Lifespan: 70,000 hr.
- IP Rating: IP65, Suitable for Wet Locations


CERTIFICATIONS: ETL











MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
FLS-10W-50K-BR	10W	100~130VAC	950LM	5000K
FLS-10W-30K-BR	10W	100~130VAC	950LM	3000K
FLS-10W-50K-WH	10W	100~130VAC	950LM	5000K
FLS-10W-30K-WH	10W	100~130VAC	950LM	3000K

LIGHTING SPECIFICATIONS:

• Driver: Non-dimmable driver

Source: COB

Total lumens: 950LM

• Cord type: 13" #18 AWG stranded wires

• Color temperature: 5000K/3000K

Color rendering index: >80

• Beam Angle: 100°

WARRANTY: 7 years

