Product Data Sheet

Magnetic Multi-Purpose LED RetroFit Kits for Upgrading Vapor Tight Light Fixtures

Engineered Products Company's (EPCO) Magnetic Multi-Purpose LED RetroFit Kits are specifically intended for upgrading Vapor Tight Light Fixtures currently using fluorescent lamps and converts them into LED Luminaires.

The building owner or facility manager can immediately lower their energy consumption, improve the quality of their lighting system, and provide long-term sustainable savings up to 40% or more.

These Kits are a premium and affordable retrofit solution to update your older 4- or 8-foot* Fluorescent Vapor Tight Light Fixtures into LED Luminaires compared to purchasing and installing a new lighting system.

Features

- High Efficiency 138 Lumens per Watt.
- Operates on 120-277-line voltage.
- Magnetic Mounting Options for fast field retrofits.
- Attaches directly to the Vapor Tight Light Fixture gear tray.
- 100,000 Hour Rated Life.
- Can be integrated with virtually all lighting systems.
- Choice of two (2) High Lumen Output color temperatures: 4000K and 5000K.

Benefits

- Lowers lighting system energy consumption up to 40%.
- Existing Vapor Tight Light Fixture gear tray can be used.
- Ready to install out of the box.
- Fast installation (approximately 8-10 minutes per Vapor Tight Light Fixture).
- Eliminates the purchase of new light fixtures.
- 1 2 Day lead time.
- Complies with local and National energy regulations.
- ETL Listed.
- Five (5) Year Warranty. For warranty information visit www.engproducts.com.
- Meets the requirements of the 2020 National Electrical Code: Articles 410.10(A), 410.104(A), 410.130(G)(1), 547.5(C)(1)(2), and 547.8(A)(B).

Contractor Advantages

- Upgrade to solid-state lighting technology.
- Manufactured using premium, high quality, solid-state components.
- Existing Vapor Tight Light Fixture housing is re-used.
- Long-term, sustainable lighting system.
- Shipped ready for immediate installation.
- Lower installed cost.
- 100% Factory tested before shipping. No contractor callbacks!

*Note: To Retrofit an 8-Foot Light Fixture, two (2) kits are required.



Frosted Smooth Diffuser (Optional Accessory) Note: Will not fit ALP Style Fixture Housings



TYPICAL APPLICATIONS

The Magnetic Multi-Purpose LED RetroFit Kit for Vapor Tight Light Fixtures replaces traditional fluorescent lamps in a variety of commercial applications, including:

Offices

LibrariesAirports

- Lobbies
- Hallways
- Conference Rooms
- ShowroomsHospitality Environments

Schools

| Specifications | | | | | | | | |
|-----------------------------|--|---------------------|--|--|--|--|--|--|
| | P/N: G4LED-RF-C4151 | P/N: G4LED-RF-C5051 | | | | | | |
| Lumen Output | 6,732 | 6,800 | | | | | | |
| Color Temperature | 4000K | 5000K | | | | | | |
| Efficacy | 137 lm/W | 138 lm/W | | | | | | |
| Voltage | 120-277 VAC | | | | | | | |
| Wattage | 51-Watts | | | | | | | |
| Color Rendering Index (CRI) | 80 Minimum | | | | | | | |
| Dimming | 0-10 Volts @ 10-100% Output | | | | | | | |
| Applications | Suitable for use in all Damp and Wet Location Vapor Tight Light Fixtures | | | | | | | |
| Operating Temperature | -40°F (-40°C) to 131°F (55°C) | | | | | | | |
| Warranty | 5-Years or 50,000 Hours | | | | | | | |
| Length | 4-Feet | | | | | | | |
| Fluorescent Lamp Equivalent | Replaces Three (3) F32 T8 Fluorescent Lamps | | | | | | | |
| Certifications | ETL Listed | | | | | | | |

PART NUMBERS

| Catalog Number | UPC Number | Description | Order Unit | Unit Qty | Unit Pkg | Units/ Case | TL Case Qty | Min Order Qty | MM Req | Ship Wt (Lbs) |
|-------------------|---------------|--|---------------|-------------|-------------|----------------|----------------|------------------|-----------|------------------|
| G4LED-RF-C4151 | 25392 | Magnetic Multi-Purpose LED RetroFit Kit for Vapor Tight Light Fixtures, 4000K Color Temperature | EA | 1 | ВХ | 1 | 1 | 1 | No | 3 |
| G4LED-RF-C5051 | 25394 | Magnetic Multi-Purpose LED RetroFit Kit for Vapor Tight Light Fixtures, 5000K Color Temperature | EA | 1 | ВХ | 1 | 1 | 1 | No | 3 |
| Accessories | | | | | | | | | | |
| GFF-DS4 | 14582 | Vapor Tight - Frosted Smooth Diffuser, 4-FT | EA | 1 | BX | 5 | 5 | 5 | No | 10 |
| GFF-DS8 | 14583 | Vapor Tight - Frosted Smooth Diffuser, 8-FT | EA | 1 | ВХ | 5 | 5 | 5 | No | 21 |

UNITS OF MEASURE KEY

Order Unit: The Unit to be ordered; Order Qty: Number of pieces in each Unit; Unit Pkg: Packaging types - BG (Bag), BX (Box), BRL (Barrel); Units/Case: Unit packages contained in the Case; TL Case Qty: The total number of items in each Master Case; Min Order Qty: The smallest Unit that can be ordered; MM Req: Must order multiples of the Unit in the stated quantities; Ship Wt (Lbs): Total weight of the units per Carton





