

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes non-shunted(rapid start) sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty



Flex™


Internal Driver LED FT Lamp

Commercial Grade LED FT Lamp

Specification Data

Model No.	Replace	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Lamp Efficacy	Life (hours)
LT24W/830-ID	FT24W	10	120-277	3000	1100	83	110	50000
LT24W/835-ID	FT24W	10	120-277	3500	1100	83	110	50000
LT24W/840-ID	FT24W	10	120-277	4000	1100	83	110	50000
LT24W/850-ID	FT24W	10	120-277	5000	1100	83	110	50000

Wiring Diagram



Dimension

Model No.	Length (inches)	Width (inches)	Height (inches)
LT24W/830-ID	12.60	1.73	0.94
LT24W/835-ID	12.60	1.73	0.94
LT24W/840-ID	12.60	1.73	0.94
LT24W/850-ID	12.60	1.73	0.94

DLC Information

Model No.	DLC Product ID	DLC Product Model	DLC Version
LT24W/830-ID			
LT24W/835-ID			
LT24W/840-ID			
LT24W/850-ID			