

LED OMNIDIRECTIONAL A-LAMP
ENCLOSED RATED A-LAMP
JA8 SERIES



5W, 9W & 12W



PRODUCT DESCRIPTION:

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescent. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

FEATURES:

- 5W, 450lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 12W, 1100lm, 75W Inc. replacement
- Dimmable down to 10 percent
- Power factor: ≥ 0.90
- 25,000 hour life (L70 standards)
- CRI: ≥ 90
- Supports Compliance of JA8-2016-E
- Supports Compliance of CEC Title 20
- Suitable for dry and damp locations
- Suitable in fully enclosed luminaires

APPLICATIONS

- Pendants
- Table and floor lamps
- Sconces

WARRANTY:

5-year standard warranty
(further details available at www.maxlite.com/warranties)
Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.



ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: E9A19D927/JA8	
	D		JA8
E5A19= 5 watts, A19 E9A19= 9 watts, A19 E12A19= 12 watts, A19	D= Dimmable	927= 2700K 930= 3000K	JA8= Supports compliance of JA8-2016-E

SPECIFICATIONS:

ITEM	SPECIFICATION	DETAILS		
		E5A19D9xx/JA8	E9A19D9xx/JA8	E12A19D9xx/JA8
GENERAL PERFORMANCE	Power Consumption	5W	9W	12W
	Lumens Delivered	450	800	1100
	Efficacy (lm/w)	90	88	91
	CRI	≥90		
	Color Temperature (CCT)	2700K, 3000K		
	Lumen Maintenance (L70)	25,000 Hours		
ELECTRICAL	Power Factor	≥0.9		
	Input Voltage	120V		
PHYSICAL	Base Type	E26		
	Operating Temperature	-4°F - 104°F		
CERTIFICATION	Certification	RoHS Compliant		
	Environment	Dry, Damp, Enclosed, JA8-2016-E		
	Warranty	5 year warranty		

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
E26 Base									
14099798	E5A19D927/JA8		5	40W Inc.	450	90	92	2700K	2.36" x 4.25"
14099800	E9A19D927/JA8	★	9	60W Inc.	800	88	92	2700K	
14099801	E9A19D930/JA8	★	9	60W Inc.	800	88	92	3000K	
14099802	E12A19D927/JA8	★	12	75W Inc.	1100	91	92	2700K	
14099803	E12A19D930/JA8	★	12	75W Inc.	1100	91	92	3000K	



NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Specifications are subject to change without notice.

COMPATIBLE DIMMERS (E5A19D99XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	603-6631-A
	6631
	6631-A
	6631-LA
	6672
	6683
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
LUTRON	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH
	DVWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAXXIMA	MEW-DM600

COMPATIBLE DIMMERS (E9A19D9XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A
	6631-A
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
	LUTRON
AYCL-153PH	
DVCL-153P-WH	
DVWCL-153PH-WHC	
S-603PH-WH	
SCL-153PH-WH	
TGCL-153PH-WH	
MAAXXIMA	MEW-DM600

COMPATIBLE DIMMERS (E12A19D9XX/JA8):

MANUFACTURE	DIMMER MODEL
AH	SDM/600
	SDM3/1000
GE	18024
LEVITON	6631
	6672
	6683
	603-6631-A
	6631-A
	6631-LA
	6683-10Z
	IPI06-1LZ
	IPI10-1LZ
	IPL06
LUTRON	AYCL-153P-WH
	AYCL-153PH
	DVCL-153P-WH
	DVWCL-153PH-WHC
	S-603PH-WH
	SCL-153PH-WH
	TGCL-153PH-WH
MAXXIMA	MEW-DM600

Specifications are subject to change without notice.