

FL1224 FL1248

Linear Ceiling Fixture



Features

Housing

Die-formed Cold-rolled Steel
 Finish Option: -62 Satin Nickel, -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity

Electrical

High Power Factor, Low THD

Lamp

Built-in LED Type: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
 Color Temperature Option – 3000K, 3500K, 4000K, 5000K


CFL Type: T8 Lamp

Certifications

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Voltage	LED CT	CRI	Lumen (Typ)	Dimension (L X W X H)	Energy Star
FL1224D-3000K	120V ~ 277V	36W	3000K	> 80	2850	24.2" x 11.5" x 4.4"	Yes
FL1224D-4000K	120V ~ 277V	36W	4000K	> 80	2950	24.2" x 11.5" x 4.4"	Yes
FL1248D-3000K	120V ~ 277V	64W	3000K	> 80	5200	48.3" x 11.5" x 4.4"	Yes
FL1248D-4000K	120V ~ 277V	64W	4000K	> 80	5300	48.3" x 11.5" x 4.4"	Yes

T8 Type

Model	Input Voltage	Finish	Shade	Lamp	Dimension (L X W X H)	Energy Star
FL1224-62	120V	Satin Nickel	Acrylic	3 x F17T8, 17W	24.2" x 11.5" x 4.4"	---
FL1248-62	120V	Satin Nickel	Acrylic	3 x F32T8, 32W	48.3" x 11.5" x 4.4"	---