

CBW

LED Curved-Basket Linear Wrap Luminaire

The Alphalite CBW Series provides high performance light levels for commercial, industrial, retail and residential applications.

Features

- · Low profile design
- High efficacy
- · Long life
- · Smooth and comfortable light without glare

Benefits

- Easy handling and storage
- · Reduces maintenance cost
- Lowers energy cost
- High quality light for a more productive space
- Easy access to standard components

Application

Ideal for corridors, hallways, stairwells, storage rooms and spaces that demand high quality lighting.



PRODUCT NUMBER BUILDER

Example: CBW-4L(40S2)/840

Series	Size	Lumens	CRI	CCT	Input Voltage	Dimming	Options
CBW							
CBW - LED Curved Basket Linear Wrap Luminaire	4 - 4′	VL - Very Low Wattage L - Low Wattage H - High	8 - 82+ CRI		120V-277V	(Blank) - 0-10V Continuous Dimming	Controls PIR - On/off PIR High Bay motion sensor PIRD - On/off PIR High Bay motion and daylight sensor MMS - Step dimming microwave motion sensor DMMSDL - Step dimming microwave motion sensor
		Lumen VH - Very High Lumen *See energy data for details					and daylight harvesting DL - Integrated Daylight harvesting SMC - Smart Control System OS - Step dimming PIR motion sensor and daylight sensor(Requires OS-618-RC101 Sensor Configuration Tool. Not included.). FCJS0 - Lutron Vive Attached fixture control Emergency Backup Lumen will maintain over the 90-minute duration EM700 (700lm), EM1400 (1400lm), EM2000 (2000lm) Assembly in USA BAA - Assembly in USA

LUMEN PACKAGES

CBW-4

CBW-4VL(22S2): 22W, 2970 lm CBW-4L(40S2): 40W, 5200 lm

CBW-4L(40/34/28S2): 40/34/28W, 5200/4420/3640 lm * Factory setting at highest lumen package

CBW-4H(46S2): 46W, 5980 lm CBW-4VH(54S2): 54W, 7020 lm

DIMENSIONS

CBW-4

9.48 lbs.



