# Contractor Series LED PAR16 (MR16) Lamp

# GU10 Base



Contractor Series LED PAR16 (MR16) lamps last over 3 times longer than halogen PAR16 lamps and are a high quality replacement for 35W halogen PAR16 lamps. They are free of UV and IR radiation, minimizing discoloration and fading of materials. These LED lamps will reduce energy and maintenance cost when compared with conventional halogen light sources.

#### **Key Features & Benefits**

- Life: rated up to 11,000 hours ( $L_{70}$ )
- GU10 Base
- Dimmable
- Available in 3000K color temperature
- UV and IR free

- Suitable for indoor use only
- RoHS compliant
- Mercury and lead free
- Lasts over 3 times longer than halogen lamps
- No warm-up time, instant-on with full light output and stable color









#### **Product Offering**

Ordering Abbreviation	Wattage	Beam Angle
PAR16	5	36°
PAR16	4	35°

#### **Application Information**

## Applications

- Recessed downlighting
- Track lighting
- Wall washers

# **Market Segments**

- Art galleries and museums
- Hospitality
- Offices
- Residential
- Restaurants
- Retail

## **Application Notes**

- 1. Operating temperature range between -4°F and +104°F (-20°C and +40°C) 5W
- 2. Suitable for indoor use only
- 3. Not intended for use with emergency light fixtures or exit lights
- 4. Use in open fixture

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.sylvania.com/fcc15b



Catalog #	Туре
Project	
Comments	
Prepared by	

## **Ordering Information**

					Input	Average		Typical				
Item	Ordering	Wattage	Base		Voltage	Rated		Lumens	CBCP		Beam	
Number	Abbreviation	(W)	Type	Replaces	(V)	Life (hrs.)1	CCT <sup>3</sup>	(lm) <sup>2</sup>	(cd)	CRI⁴	Angle	Dimmable
79274*	LED5PAR16/GU10/830/FL36/10HRBL	5	GU10	35WPAR16	120	10,000	3000K	350	650	81	36°	No
78560	LED4PAR16/GU10/DIM/830/FL35/10YV/RP	4	GU10	35WPAR16	120	11,000	3000K	350	650	81	35°	Yes

#### **Ordering Guide**


LED	4	PAR16	1	GU10	1	DIM	1	830	1	FL	35	10YV	/	RP
LED	Wattage:	Lamp Type:		Base		Dimmable		CRI, CCT:		Beam Type:	Beam	11,000		Retail
Lamps and	4	PAR16		Type:				830: 81 CRI,		FL: Flood	Angle:	hour		pack
Retrofits				GU10				3000K CCT			35°			

# **Energy Savings**

Basic Product Description	LED Life (hrs.)	Similar Halogen	Halogen Life (hrs.)	Watts Saved	Energy Savings*	LED Life vs. Halogen
LED5PAR16	10,000	35PAR16	3,000	30	\$36	3.3X
LED4PAR16	11,000	35PAR16	3,000	31	\$38	3.6X

<sup>\*</sup>Energy savings over life of lamp calculated at \$0.11/kWh

#### **Lamp Dimensions**



#### **Sample Specification**

Lamps shall be Contractor Series LED PAR16 (MR16) GU10 with a 11,000 hour average rated life. Lamps shall be energy efficient, UV & IR free. Should have a beam angle of 35 degrees.

LEDVANCE LLC 200 Ballardvale Street Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks. All other trademarks are those of their respective owners. Product Licensee of Trademark SYLVANIA in General Lighting. Specifications subject to change without notice.







<sup>\*</sup> Lamp phasing out
1. Hours lifetime with 70% lumen maintenance
2. Thermally stable typical lumens (±10%)
3. Thermally stable typical CCT (±10%)
4. CRI – Color Rendering Index