PROJECT:	TYPE:
LOCATION:	CAT:

#### Description

The Mini Double Flange extrusion is perfect for shallow recessed applications with 1/8" flanges on either edge for a finished look.

#### Features

- Extruded aluminum construction
- Use tape light, lens, and end caps to create a complete fixture (tape light and accessories sold separately)
- · Not compatible with jacketed tape light when using a lens

## Mounting

Recess mount via  $3M^{\circ}$  double-sided adhesive tape or construction adhesive; Fits in  $5/8^{\circ}$  wide x  $1/4^{\circ}$  deep channels

## **Applications**


Stairs, handrails, display shelving and cases, niche and accent lighting


### Warranty

3 years

## Technical Information

**Profile Dimensions** 





# Ordering Information



### PE-AA1DF-1M includes:

(1) 1M Mini Double Flange extrusion

\*Mini Double Flange Slot Channel is available as special order only Please allow up to 2 weeks for order processing.

## Accessories

Image	Part Number	Description
	PE-UVLENS-1M	1 meter frosted polycarbonate lens for Mini Double Flange extrusion; UV Resistant/Flame Retardant
	PE-AA1DF-END	Polypropylene plastic end cap for Mini Double Flange extrusion
31,31,31,3	ЗМ-ТАРЕ-10	1/2" x 4" Length Strips of 3M° double-sided adhesive tape (Bag of 10)