

# TRULUX HIGH OUTPUT - 24V



## Trulux High Output Tape Light & Accessories

Use high output Trulux tape light and extrusions to build your own task lighting systems or custom linear lighting fixtures. Light output ranges from 220-310 lumens per foot, with easy to work with run lengths up to 22 feet. Wall controls include dial or touch versions; or use the Trulux App for even greater control freedom.

### Features

- Excellent color rendering (94+ CRI) creates a natural light that shows colors accurately
- Color temperatures available from 2400K to 4000K
- 220-310 lumens per foot performance combines well with specialty extrusions to build custom linear fixtures using only 4.4 watts/foot (see Trulux Extrusions on pages 38-55)
- Dimmable with most electronic low voltage (ELV) dimmers
- Run lengths up to 22 feet
- IP54 tape is cuttable every 3.94" while maintaining cULus safety rating
- 2835 LEDs last up to 50,000 hours rated life
- For additional information on High Output IP68 Trulux, see pages 21-23

### Applications

- |                 |              |                 |
|-----------------|--------------|-----------------|
| • Edge lighting | • Cloves     | • Railings      |
| • Cabinetry     | • Staircases | • Task lighting |
| • Shelving      | • Toe kicks  | • Display cases |





2400K Deluxe Warm White 4.4W per ft / 285Lm per ft	2700K Ultra Warm White 4.4W per ft / 285Lm per ft	3000K Warm White 4.4W per ft / 292Lm per ft	4000K White 4.4W per ft / 310Lm per ft
--	---	---	--

HTL-UWX (16.4ft)	HTL-UWW (16.4ft)	HTL-WW (16.4ft)	HTL-WH (16.4ft)
------------------	------------------	-----------------	-----------------



Unavailable	Unavailable	HTL68-WW (16.4ft)*	HTL68-WH (16.4ft)*
-------------	-------------	--------------------	--------------------

\*For additional product information, please see page 9; for submersible applications, please see pages 20-23

## Power Accessories



**SRF-BATT**  
Trulux RF Wall Dimmer  
Single zone  
(Battery operated)



**SRF-4Z-3P**  
Trulux RF Wall Dimmer  
1-4 zones  
(24V DC input)



**REC-5A-4Z-WiFi**  
Trulux RF / WiFi Receiver  
1-4 zones  
(24V DC input)



**REC-5A-4Z**  
Trulux RF Receiver  
1-4 zones  
(24V DC input)



**LED-DR30-24 (30W)**  
24V Trulux System Driver  
cURus (dry)



**LED-DR60-24 (60W)**  
**LED-DR-100-24 (100W)**  
**LED-DR-150-24 (150W)**  
24V Trulux System Drivers  
cURus (wet)



**ELV-30-24 (30W)**  
**ELV-45-24 (45W)**  
24V Non-Trulux dimming  
Drivers, cETLus (dry)



**ELV-60J-24 (60W)**  
**ELV-80J-24 (80W)**  
24V Non-Trulux dimming  
Drivers, cETLus (wet)



**TL-2PWR**  
Power feed snap  
connector to bare wires  
(IP54 reel includes 3)



**TL-2DC**  
Power feed snap  
connector to DC jack  
(IP54 reel includes 3)



**TL-2JUMP-.5 (6")**  
**TL-2JUMP-1 (12")**  
**TL-2JUMP-2 (24")**  
Tape-to-tape jumper



**TL-2SPL**  
In-line splice  
connector



**TL-2L**  
L connector



**TL-2T**  
T connector



**TL-2X**  
X connector



**TL-2FCON68**  
24" Power feed - IP68  
Female connector



**TL-2JUMP68-10 (10ft)**  
**TL-2JUMP68-20 (20ft)**  
Power-to-power - IP68  
Jumper



**TL-CLIPS-15**  
Mounting clips - IP68  
(Qty of 15)