PAR30S-11-927-25D-DIM

RAB[®] Lamps



Project:		Туре:		
Prepared	I Ву:	Date:		
Driver Info	ver Info LED Info			
Watts	11W	Input Voltag	je 120V	
Color Temp	2700K (Soft White)	Power Fact Flicker	or 0.9 <30%	
Lumens	900	THDi	N/A	
Efficacy	81.8 LPW	R9	50	
Color Accurac	y 90 CRI	-		
L70 Accuracy	40,000			


Technical Specifications

Listings	Technical Specifications	MOL (inches):
UL Listed:	Dimmable:	3.54"
Yes	Yes, down to 10%	MOD (inches):
FCC:	Description	3.74"
Yes	R9:	LED Characteristics
T24:	50	Lifespan:
Complies with Title 24 Appendix JA8	Lamp Type:	40,000-hour LED lifespan based on IES LM-70
Rohs:	Par	results
Yes	Bulb Type:	Other
CEC Status:	PAR30S	Equivalent:
Lawful for sale in California	Base Type:	75W Halogen PAR30S
ENERGY STAR V2.0:	E26, Medium Screw Base	Warranty:
This product is ENERGY STAR® Version 2.0	Material:	4 years
Certified	Plastic	
Energy Star ID:	Construction	
2328358	Operating Temparture:	
	-20 - 45°C	

PAR30S-11-927-25D-DIM

Optical	Shipping Information	Pallet Quantity of Pieces:
eam Angle:	Case Qty:	840
5°	6	Pallet Dimensions:
IBCP:	Case Dimensions:	46.654 x 38.386 x 37.795
910	12.8 x 8.46 x 4.72	

Dimensions



Features

PAR REPLACEMENT - Replaces conventional PAR lamps ENERGY SAVINGS - Save up to 85% on energy DAMP RATED - Suitable for damp locations ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures DIMMABLE - Compatible with most common dimmer models SHATTERPROOF - Plastic lamps for rugged applications 90 CRI - Produces rich and vibrant colors

Ordering Matrix

Family	Neck	Lamp Power	CRI/Color Temp	Beam Angle	Dimmable
PAR30	S	11	927	25D	DIM
	S = Short	11 = 75W	927 = 2700K 930 = 3000K 940 = 4000K 950 = 5000K	25D = 25 degrees 40D = 40 degrees	DIM = Dimmable